

Declaration of Performance

Nr. D100-01

1. **Product-type identification:** Extruded Ceramic Tiles, with water absorption $E_b \le 0.5\%$

2. Intended use: For internal and external walls and flooring

3. Manufacturer: Vitra Karo Sanayi ve Ticaret A.Ş.

E-5 Karayolu Üzeri Şifa Mah. Hükümet Caddesi No.5

34941 Tuzla İstanbul -TÜRKİYE

4. Authorised representative: Vitra Fliesen GmbH & Co.KG

Brucknerstraße 43 D-56566 Neuwied Deutschland

5. System of assessment and verification of

constancy performance:

System 4

6. Declared performance:

Essential characteristics	Performance	Harmonised technica specification
Reaction to fire	A1 / A1 _{FL}	EN 14411: 2012
Release of dangerous substance, for:		
- Cadmium	NPD / No Performance Determined	EN 14411: 2012
- Lead	NPD / No Performance Determined	EN 14411: 2012
- Other	NPD / No Performance Determined	EN 14411: 2012
Breaking strength	\ge 1300 N for thickness ≥ 7,5mm \ge 600 N for thickness < 7,5mm	EN 14411: 2012
Slipperiness -Tested according to EN 16165	See note 1	EN 14411: 2012
Tactility	NPD / No Performance Determined	EN 14411: 2012
Bond strength/adhesion for:		
- Cementitious adhesive, type C2	NPD / No Performance Determined	EN 14411: 2012
- Dispersion adhesive	NPD / No Performance Determined	EN 14411: 2012
- Reaction resin adhesive	NPD / No Performance Determined	EN 14411: 2012
- Mortar	NPD / No Performance Determined	EN 14411: 2012
Thermal shock resistance	Pass	EN 14411: 2012
Durability For:		
-Internal Use	Pass	EN 14411: 2012
-External Use: freeze-thaw resistance	Pass	EN 14411: 2012

Note 1-Only necessary when required by corresponding national statutory regulations; for product-specific data see technical information In VitrA product catalogue and technical documents

Signed for and on behalf of the manufacturer by:

Bayram Bülent Maşa – Quality Assurance Manager Name and Function

BOZÜYÜK – 01/11/2023 Place and date of issue Signature

^{7.} The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.